AUTOPULSE 320-T3

15 → 320 A

Ref. 067615



AUTOPULSE 320-T3 is a digital MIG/MAG double pulse generator with 3 integrated wire feeders. It is an extremely advanced machine with 68 synergic curves providing an exceptional arc quality. Versatile, it will hold 3 different torches to weld steel, aluminium and brazing (CuSi3/CuAl8). The user friendly interface and the very precise wire feed make the quality of the weld on very thin sheets outstanding.

MIG/MAG OPTIMISED SETTINGS

- Welding processes: Standard, Pulse, Pulse in Pulse, and Manual.
- **Trigger activation modes :** 2T, 4T, SPOT, DELAY and TACK function.
- **Precise control over the welding cycle :** CreepSpeed, Softstart, Hotstart, Upslope, Downslope, Crater Filler, Postqaz, etc.

■ MIG/MAG welding:

- steel wire Ø 0.6 / 1.0 mm
- stainless steel wire Ø 0.8 / 1.0 mm
- aluminium wire Ø 0.8 / 1.0 / 1.2 mm

■ Brazing mode:

- wire CuSi and CuAl Ø 0.8 / 1.0 mm

SIMPLIFIED WELDING

- The **68 synergic curves** guarantee an outstanding weld using a large range of materials, wire sizes and gases.
- The **integral synergic mode** determines automatically the best welding settings but also allow the user to adjust them (wire feed speed, voltage, current, self).

MAXIMUM PRODUCTIVITY

- **4 microprocessors** increase the calculation speed and general machine efficiency.
- Very high arc voltage guarantee an easy arcing and an exceptional arc performance on all types of metals.
- **3 electronically** regulated wire feeders fitted with 4 drive rolls each.
- Will hold up to 3 wire reels of 200mm diameter.
- **Automatic detection of the torches** when the trigger is pressed.
- Over hanging torch support (x3) and welding helmet.
- Compatible with Push Pull torches (24 V).
- Compatible with Spool Guns and ideal for aluminium soft wire (AlSi5 / AlSi12).

USER FRIENDLY INTERFACE

- New and simplified interface designed specifically for use by bodyshop staff.
- **Colour screen XL** to set and control the welding cycle very precisely.
- 2 scroll wheels and 4 buttons to easily navigate through the different menus.
- **Complete update** of the machine and its programs through a simple USB stick.
- Storage available for up to **500 welding programs** for repetitive jobs.

ROBUST AND MOBILE

- Reinforced casing.
- IP23 protection rated.
- Low base suitable for 2 gas bottles (2x4m3).

Delivered with 3 torches (250 A - 3 m):

- MIG/MAG torch (Ø 1.0)
- MIG/MAG torch (Ø 0.8)
- ALU torch (Ø 1.2)
- + over hanging torch support included



3 levels of customer interface:

- EASY (simplified module)
- **EXPERT** (complete module)
- AVANCÉ (specific applications)

ACCESSORIES (OPTIONS)







Box of contact tips MB15 / MB25 - 250 A 037458

•	- AM-	~	⊕ *	@ 1	③	ф	équipé d'origine / original equipement / originalausstatung / equipamiento de fabrica	EN 60974-1 (40°C)	U _o	_ 7	2	IP	Protected	
50/60 Hz	Α	min → max	ø mm	ø mm	Electronic Control	m/min		X (40°C)	٧	cm	kg		& compatible power generator (+/-15%)	
400 V 3~	16	15 → 320	0.6 → 1.2	200	1 00 → 50 W	0.5 → 20	1.0 1.2	260 A @ 60% 240 A @ 100%	82.4	88 x 63 x 93	64	IP 23	24 kVA	